PRODUCT: AS01SPRY0001



1 IDENTIFICATION OF THE PREPARATION AND THE COMPANY:

PRODUCT NAME: AS01SPRY0001

INTENDED USE: Sprayable Contact Adhesive

SUPPLIER: **NEY Limited**

Stonebridge Trading Estate

Sibree Road Coventry CV3 4FD

EMERGENCY TELEPHONE: 024 7630 8100

2 COMPOSITION/INFORMATION ON INGREDIENTS:

Extremely flammable. Limited evidence of a carcinogenic effect.

CLASSIFICATION Carc 3:R40. F+:R12.

3 HAZARDS IDENTIFICATION:

Name	EC No.	CAS-No.	Content	Classification
BUTANE/ISOBUTANE		106-97-8	10-30%	F+;R12.
DICHLOROMETHANE	200-838-9	75-09-2	30-60%	Carc3;R40
PROPANE	200-827-9	74-98-6 1	0-30%	F+;R12
The Full Text for all R-Phrases are Displayed in Section 16				

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST AID MEASURES:

GENERAL INFORMATION

Move the exposed person to fresh air at once.

INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and

at rest. Get prompt medical attention.

INGESTION

Rinse mouth thoroughly. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

page 1 of 5

Important:

As most requirements are unique, it is most important that trials are carried out in order that the user satisfies themselves that the adhesive is suitable. The information given on this sheet is for guidance only and does not represent a specification.

PRODUCT: AS01SPRY0001



5 FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA

Water spray, fog or mist. Carbon dioxide (CO2). Foam.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Use water spray to reduce vapours. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Forms explosive mixtures with air. Extremely flammable. May explode in a fire. May travel considerable distance to source of ignition and flash back.

6 ACCIDENTAL RELEASE MEASURES:

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers. Use sealed containers for reclamation or disposal in licensed special waste. Avoid contact with water.

7 HANDLING AND STORAGE:

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION:

<u>Name</u> <u>Std</u> <u>TWA - 8 hrs</u> <u>STEL - 15 min</u> <u>Notes</u>

BUTANE/ISOBUTANE WEL 600 ppm 750 ppm

DICHLOROMETHANE WEL 100 ppm (Sk) 350 mg/m³ (Sk) 300 ppm (Sk) 1060 mg/m³ (Sk)

WEL = Workplace Exposure Limit.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

SKIN PROTECTION

Wear suitable gloves if prolonged or repeated skin contact is likely.

Important: page 2 of 5

PRODUCT: AS01SPRY0001



9 PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE

Aerosol container containing a mixture of active ingredients, solvents and propellants.

ODOUR

Of solvents

PHYSICAL DATA COMMENTS

A flash point method is not available for aerosols but the major hazardous component the Propellant has a flash point of <-40 C with flammability limits of 9.5% volume. Upper and 1.8% vol. lower. Auto ignition temperature is 410/580 C.

10 STABILITY AND REACTIVITY:

STABILITY

Highly volatile

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION:

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Known or suspected carcinogen for humans.

HEALTH WARNINGS

Prolonged inhalation of high concentrations may damage respiratory system. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

ROUTE OF ENTRY

Inhalation. Skin absorption.

TARGET ORGANS

Central nervous system. Respiratory system, lungs. Liver.

MEDICAL SYMPTOMS

Narcotic effect. Drowsiness. Dizziness.

Name BUTANE/ISOBUTANE

12 ECOLOGICAL INFORMATION:

ECOTOXICITY

The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS

Ensure container is empty and dispose of in accordance with Local Authority regulations. Do not pierce or incinerate even when container is empty.

page 3 of 5

As most requirements are unique, it is most important that trials are carried out in order that the user satisfies themselves that the adhesive is suitable. The information given on this sheet is for guidance only and does not represent a specification.

PRODUCT: AS01SPRY0001



14 TRANSPORT INFORMATION:

GENERAL

This product is packed in accordance with the Limited quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.

UK ROAD CLASS 2

PROPER SHIPPING NAME Flammable Gas (class 2) UN NO. ROAD 1950 UK ROAD PACK GR. 2.1

15 REGULATORY INFORMATION:

LABELLING





Harmful Extremely Flammable CONTAINS DICHLOROMETHANE

RISK PHRASES

R12 Extremely flammable.

R40 Limited evidence of a carcinogenic effect.

SAFETY PHRASES

S9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition - No smoking.

S51 Use only in well-ventilated areas.

S36/37 Wear suitable protective clothing and gloves.

S60 This material and its container must be disposed of as hazardous waste.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 1988. Chemicals (Hazard Information & Packaging) Regulations.

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Health and Safety at Work Act (As Amended)

1974 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

Important: page 4 of 5

PRODUCT: AS01SPRY0001

NEY Limited
Stonebridge Trading Estate
Sibree Road
Coventry CV3 4FD

T: 024 7630 8100
F: 024 7630 8102
E: materials.info@ney.co.uk

www.ney.co.uk

16 OTHER INFORMATION:

RISK PHRASES IN FULL R12 Extremely flammable. R40 Limited evidence of a carcinogenic effect.